



HBLEMC3MS

Highbay Emergency Converter

FEATURES

IP rating	IP65
IK rating	IK08
Emergency Option	Yes, Manual & Self-Test

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C to +40°C
Weight	1.3
Inrush Current	6A
Construction Material	PC & Steel
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	I
Battery	LiFePO4 6.4V 5500mAh
Install Connector Type	Flying lead
Power Factor	0.35

PHOTOMETRICS @ 25°C

Product code	Finish	W	EM lm
HBLEMC3MS	Black	6W	1000

ACCESSORIES

Area Bay	All variants	Sold Separately
Springbok Lite	All variants	Sold Separately
GenBay	All variants	Sold Separately
Area Bay Switch	All variants	Sold Separately

Self-test and Manual-test
switchable

IP65 for exterior and interior
installations

A minimum of 3 hours of
emergency lighting

WARRANTY

Warranty	5 years
Battery Warranty	5 years

FEATURES & BENEFITS

Dedicated LED module provides 1000lm

In-line-mounted unit to keep your installation
tidy

Can be mounted separately from a highbay
luminaire

BEAM ANGLE:

