



IK10 for a robust fitting



CCT Switchable between 2200K & 3000K



Wattage Switchable between 14W, 19W & 24W

Hydra Bollard

Features

IP rating	IP65
IK rating	IK10
CSP Switchable	Switchable CCT
Sensor Option	Photocell
Dimmable Option	No
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 45°C
Weight	2kg
Inrush Current	30A 0.15ms
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	No
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty	5 years
Battery Warranty	3 years


Features & benefits

- Interchangeable top head provides easy maintenance
- Choice of cone or opal aesthetics & light distribution
- CCT switch set to 3000K as default
- New 2200K to minimise effects of blue light
- Must be sold with HYBxBOLLARD
- Switch live out function with photocell not possible

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
HYBICONEB	Black	Standard	360°	14W	2200K	1000	71	AIGD
					3000K	1150	82	
				19W	2200K	1400	74	
					3000K	1500	79	
				24W	2200K	1700	71	
					3000K	1800	75	
HYBICONES	Silver	Standard	360°	14W	2200K	1300	93	AIGD
					3000K	1500	107	
				19W	2200K	1800	95	
					3000K	1950	103	
				24W	2200K	2250	94	
					3000K	2400	100	
HYBIOPALW	White	Standard	360°	14W	2200K	1050	75	AIGD
					3000K	1200	86	
				19W	2200K	1450	76	
					3000K	1550	82	
				24W	2200K	1750	73	
					3000K	1900	79	
HYBICONEBPC	Black	Photocell	360°	14W	2200K	1000	71	AIGD
					3000K	1150	82	
				19W	2200K	1400	74	
					3000K	1500	79	
				24W	2200K	1700	71	
					3000K	1800	75	
HYBICONESPC	Silver	Photocell	360°	14W	2200K	1300	93	AIGD
					3000K	1500	107	
				19W	2200K	1800	95	
					3000K	1950	103	
				24W	2200K	2250	94	
					3000K	2400	100	
HYBIOPALWPC	White	Photocell	360°	14W	2200K	1050	75	AIGD
					3000K	1200	86	
				19W	2200K	1450	76	
					3000K	1550	82	
				24W	2200K	1750	73	
					3000K	1900	79	

Ø160mm



Wirina Information



collingwood

Built to endure (IK10 impact rating), the Hydra Bollard offers superior durability for illuminating pathways and public areas. This bollard has adjustable lighting with switchable colour temperature (2200K for minimal blue light or 3000K) and wattage (14W, 19W, 24W) to meet your specific needs. An interchangeable top head in cone or opal styles provides focused or diffused light, making maintenance easier.

Cable Required for Connector	3x 0.75 - 2.5mm ²
Type of Wiring Required	Parallel

LED Driver

Driver	Input
N/A (intergrated driver)	220-240V

Accessories

HYXBOLLARD	Hydra post and ground kit	Sold Separately
HYBXROOTKIT	Hydra mounting kit for soft ground	Sold Separately
HYXBOLTKIT	Hydra expansion bolt kit for concrete	Sold Separately