

INDY K3 65-80-125W

Wattage Switchable Symmetrical Floodlight

FEATURES

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Tiltable (°)	180
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	-40°C - 40°C		
W-:	IFLB1N: 2.5kg IFLB2N:		
Weight	4.5kg IFLB3N: 7.1kg		
	IFLB1N: 30.3A 0.22ms		
Inrush Current	IFLB2N: 53A 0.22ms IFLB3N:		
	30.3A 0.22ms		
Construction Material	Die-cast aluminium (body)		
Construction Material	stainless steel 304 (bracket)		
SELV	No		
Electric Class (1, 2, 3)	I		
Install Connector Type	Flying lead		
UK Building Regulations	Part P		
Power Factor	0.95		

Photometrics @ 25°C

Product Code	Finish	Beam	w	Colour	lm	lm/W	lx@1m	Energy
IFLB1N40 Black			65W	4000K	10000	154	3521	
	120°	80W	4000K	12500	156	3521	A D G	
		125W	4000K	19500	156	3521		
IFLB1N30 Black			65W	3000K	9500	146	4225	
	120°	80W	3000K	12000	150	4225	A E	
			125W	3000K	19000	152	4225	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead 1000mn	H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required Parallel	

ACCESSORIES

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately



LIGHTING INNOVATION



High efficacy up to 156lm/W



Wattage switchable between 65-125W



Suitable for use in coastal applications

WARRANTY

Warranty
On-Site Warranty

2 years

FEATURES & BENEFITS

Quick and easy installation with angle stamped prackets

Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications

Compatible with the PCELLKIT dusk to dawn sensor

6kV Surge Protection

Asymetrical floodlights also available in K2 product range

Suitable for mounting upside down as an uplight



