

# INDY K3 125-165-200W

Wattage Switchable Symmetrical Floodlight

#### **FEATURES**

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Tiltable (°)	180
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

#### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 40°C
W-i-b+	IFLB1N: 2.5kg IFLB2N:
Weight	4.5kg IFLB3N: 7.1kg
	IFLB1N: 30.3A 0.22ms
Inrush Current	IFLB2N: 53A 0.22ms IFLB3N:
	30.3A 0.22ms
Construction Material	Die-cast aluminium (body)
Construction Material	stainless steel 304 (bracket)
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Flying lead
UK Building Regulations	Part P
Power Factor	0.95

### Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
			125W	4000K	19500	156	6822	
IFLB2N40	Black	120°	165W	4000K	25000	156	6822	A D
		200W	4000K	27500	152	6822		
IFLB2N30 Black 120°		125W	3000K	19000	152	6647		
	120°	165W	3000K	24500	148	6647	A G	
		200W	3000K	27000	135	6647		

Energy rating is a reflection of the LED light source.

#### WIRING INFORMATION

Type of Wiring Required Parallel	Cable / Flying Lead	1000mm H05RN-F 3x1.0mm² Ø7mm
Type of Willing Required	Type of Wiring Required	Parallel

#### **ACCESSORIES**

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately



LIGHTING INNOVATION



High efficacy up to 152lm/W



Wattage switchable between 125-200W



Suitable for use in coastal applications

#### WARRANTY

Warranty
On-Site Warranty

5 years 2 years

## FEATURES & BENEFITS

Quick and easy installation with angle stamped brackets

Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications

Compatible with the PCELLKIT dusk to dawn sensor

6kV Surge Protection

Asymetrical floodlights also available in K2 product range

Suitable for mounted upside down as an uplight



