

INDY K3 300W

Symmetrical floodlight suitable for commercial and industrial applications

FEATURES

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Tiltable (°)	180
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 40°C
Weight	7.1kg
Inrush Current	IFLB1N: 30.3A 0.22ms IFLB2N: 53A 0.22ms IFLB3N: 30.3A 0.22ms
Construction Material	Die-cast aluminium (body) stainless steel 304 (bracket)
SELV	No
Electric Class (1, 2, 3)	I
Install Connector Type	Flying lead
UK Building Regulations	Part P
Power Factor	0.95

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
IFLB3N40	Black	300W	4000K	120°	44500	138	15420	D
IFLB3N30	Black	300W	3000K	120°	44000	147	15247	D

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm² Ø7mm
Type of Wiring Required	Parallel

ACCESSORIES

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately

COLLINGWOOD LIGHTING

LIGHTING INNOVATION

- 147lm/W — High efficacy up to 147lm/W
- 300W — High power 300W
- Suitable for use in coastal applications

WARRANTY

Warranty	5 years
On-Site Warranty	2 years

FEATURES & BENEFITS

- Quick and easy installation with angle stamped brackets
- Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications
- Compatible with the PCELLKIT dusk to dawn sensor
- 6kV Surge Protection
- Asymetrical floodlights also available in K2 product range
- Suitable for mounting upside down as an uplight

BEAM ANGLE: **120°**



