

INDY K3 300W

Symmetrical floodlight suitable for commercial and industrial applications

FEATURES

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Tiltable (°)	180
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5

INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	-40°C - 40°C		
Weight	7.1kg		
	IFLB1N: 30.3A 0.22ms		
Inrush Current	IFLB2N: 53A 0.22ms IFLB3N:		
	30.3A 0.22ms		
Construction Material	Die-cast aluminium (body)		
Construction Material	stainless steel 304 (bracket)		
SELV	No		
Electric Class (1, 2, 3)	1		
Install Connector Type	Flying lead		
UK Building Regulations	Part P		
Power Factor	0.95		

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
IFLB3N40	Black	300W	4000K	120°	44500	138	15420	A D G
IFLB3N30	Black	300W	3000K	120°	44000	147	15247	A D

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm² Ø7mm
Type of Wiring Required	Parallel

ACCESSORIES

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately



LIGHTING INNOVATION



High efficacy up to 147lm/W



High power 300W



Suitable for use in coastal applications

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Quick and easy installation with angle stamped brackets

Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications

Compatible with the PCELLKIT dusk to dawn sensor

6kV Surge Protection

Asymetrical floodlights also available in K2 product range

Suitable for mounting upside down as an uplight



