

High efficacy up to 147lm/W

High power 300W

Suitable for use in coastal applications

## FEATURES & BENEFITS

Quick and easy installation with angle stamped brackets

Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications

Compatible with the PCELLKIT dusk to dawn sensor

6kV Surge Protection

Asymmetrical floodlights also available in K2 product range

Suitable for mounting upside down as an uplight

# INDY K3 300W

Symmetrical floodlight suitable for commercial and industrial applications

## FEATURES

<b>IP rating</b>	IP65
<b>IK rating</b>	IK07
<b>Dimmable Option</b>	Yes (1-10V)
<b>LED Lifetime</b>	L70 50,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM5

## INSTALLATION INFORMATION

<b>Maximum Ambient Temperature</b>	-20°C to 40°C
<b>Construction Material</b>	Die-cast aluminium (body) stainless steel 304 (bracket)
<b>Electric Class (1, 2, 3)</b>	I

## PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
<b>IFLB3N40</b>	Black	300W	4000K	120°	44500	138	15420	
<b>IFLB3N30</b>	Black	300W	3000K	120°	44000	147	15247	

Energy rating is a reflection of the LED light source.

120°