



High efficacy up to 147lm/W



High power 300W



Suitable for use in coastal applications

## WARRANTY

Warranty	5 years
On-Site Warranty	2 years

## FEATURES & BENEFITS

Quick and easy installation with angle stamped brackets

Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications

Compatible with the PCELLKIT dusk to dawn sensor

6kV Surge Protection

Asymmetrical floodlights also available in K2 product range

Suitable for mounting upside down as an uplight

# INDY K3 300W

Symmetrical floodlight suitable for commercial and industrial applications

## FEATURES

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Tilttable	180°
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 40°C
Weight	7.1kg
Inrush Current	IFLB1N: 30.3A 0.22ms IFLB2N: 53A 0.22ms IFLB3N: 30.3A 0.22ms
Construction Material	Die-cast aluminium (body) stainless steel 304 (bracket)
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Flying lead
UK Building Regulations	Part P
Power Factor	0.95

## PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
IFLB3N40	Black	300W	4000K	120°	44500	138	15420	
IFLB3N30	Black	300W	3000K	120°	44000	147	15247	

## WIRING INFORMATION

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm² Ø7mm
Type of Wiring Required	Parallel

## ACCESSORIES

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately
----------	----------------------------	-----------------

