



High efficacy up to 152lm/W



Wattage switchable between 125-200W



Suitable for use in coastal applications

Indy K3 125-165-200W

Wattage Switchable Symmetrical Floodlight

Features

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Tilttable	180°
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 40°C
Weight	IFLB1N__: 2.5kg IFLB2N__: 4.5kg IFLB3N__: 7.1kg
Inrush Current	IFLB1N: 30.3A 0.22ms IFLB2N: 53A 0.22ms IFLB3N: 30.3A 0.22ms
Construction Material	Die-cast aluminium (body) stainless steel 304 (bracket)
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Flying lead
UK Building Regulations	Part P
UK Protection	Surge Protection 6KV
Power Factor	0.95

Guarantee

Warranty	5 years
On-Site Warranty	2 years

Features & benefits

- Quick and easy installation with angle stamped brackets
- Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications
- Compatible with the PCELLKIT dusk to dawn sensor
- 6kV Surge Protection
- Asymmetrical floodlights also available in K2 product range
- Suitable for mounted upside down as an uplight

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
IFLB2N40	Black	120°	165	4000K	25000	156	8747	
			200	4000K	27500	152	8747	
			125	4000K	19500	156	8747	
IFLB2N30	Black	120°	165	3000K	24500	148	8572	
			200	3000K	27000	135	8572	
			125	3000K	19000	152	8572	

Wiring Information

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm² Ø7mm
Type of Wiring Required	Parallel

Accessories

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately
----------	----------------------------	-----------------

