



High efficacy up to 156lm/W



Wattage switchable between 65-125W



Suitable for use in coastal applications

Indy K3 65-80-125W

Wattage Switchable Symmetrical Floodlight

Features

IP rating	IP65
IK rating	IK07
CSP Switchable	Single CCT
Tilttable	180°
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 40°C
Weight	IFLBIN__: 2.5kg IFLB2N__: 4.5kg IFLB3N__: 7.1kg
Inrush Current	IFLBIN: 30.3A 0.22ms IFLB2N: 30.3A 0.22ms IFLB3N: 30.3A 0.22ms
Construction Material	Die-cast aluminium (body) stainless steel 304 (bracket)
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Flying lead
UK Building Regulations	Part P
UK Protection	Surge Protection 6KV
Power Factor	0.95

Guarantee

Warranty	5 years
On-Site Warranty	2 years

Features & benefits

- Quick and easy installation with angle stamped brackets
- Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications
- Compatible with the PCELLKIT dusk to dawn sensor
- 6kV Surge Protection
- Asymmetrical floodlights also available in K2 product range
- Suitable for mounting upside down as an uplight

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
IFLBIN40	Black	120°	80	4000K	12500	156	4401	
			125	4000K	19500	156	4401	
			65	4000K	10000	154	4401	
IFLBIN30	Black	120°	80	3000K	12000	150	3345	
			125	3000K	19000	152	3345	
			65	3000K	9500	146	3345	

Wiring Information

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately
----------	----------------------------	-----------------

