



K2

Industrial Floodlight, up to 114lm/W, IP65 & IK08 rated

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
Tiltable	180°
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 50°C
Weight	100W - 4.00Kg 150W - 5.00Kg 200W - 5.60Kg
Inrush Current	100W - 70A 0.2ms 150W - 110A 0.2ms 200W - 120A 0.2ms
Construction Material	Aluminium alloy tempered glass
SELV	Yes
Electric Class (1, 2, 3)	1
Install Connector Type	Flying lead
UK Building Regulations	Part P
Connection Output	Flying Lead

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
IFL15BX40100150	Black	Asymmetric beam angle	150W	4000K	100°x150°	17100	114	2966	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel
Input Cable Type	3x 1.0mm ²
Series / Parallel	Parallel


LED DRIVER


SELV
Yes

ACCESSORIES

PCCELLKIT	Wall Mounted Photocell Kit	Sold Separately
-----------	----------------------------	-----------------

 114lm/W High efficacy of 114lm/W

 Quick and easy installation with angle stamped brackets

 IP65 IP65 suitable for outdoor environments

WARRANTY

Warranty 5 years

FEATURES & BENEFITS

Ratchet points on bracket, tightened by allen key

Surge protection L/N-PE = 10KV L-N = 6KV

