



High efficacy of 111lm/W



Quick and easy installation
with angle stamped
brackets



IP65 suitable for outdoor
environments

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Ratchet points on bracket, tightened by allen
key

Surge protection L/N-PE = 10KV L-N = 6KV



K2

Industrial Floodlight, up to 111lm/W, IP65 & IK08 rated

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
Tilttable	180°
Sensor Option	No
Dimmable Option	No
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-40°C - 50°C
Weight	100W - 4.00Kg 150W - 5.00Kg 200W - 5.60Kg
Inrush Current	100W - 70A 0.2ms 150W - 110A 0.2ms 200W - 120A 0.2ms
Construction Material	Aluminium alloy tempered glass
SELV	Yes
Electric Class (1, 2, 3)	1
Install Connector Type	Flying lead
UK Building Regulations	Part P
Connection Output	Flying Lead

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel
Input Cable Type	3x 1.0mm ²
Series / Parallel	Parallel

LED DRIVER

SELV	Yes
------	-----

ACCESSORIES

N/A	No accessories required
-----	-------------------------

