Decorative wall lights + undershelf lighting specification sheet



LED LYTE IP T

IP rated threaded mini LED light

Features			
IP rating	IP65		
CSP Switchable	Single CCT		
Dimmable Option	Driver dependent		
LED Lifetime	L70 70,000h		
Colour Consistency	SDCM3		

Installation Information			
Input	350mA		
Maximum Ambient Temperature	35°C		
Weight	44g		
Cut Out Size	Ø 26mm		
Construction Material	Anodised aluminium		
UK Bathroom Zone	1		
Electric Class (1, 2, 3)	3		
Suitable for coastal areas	Yes		

Photometrics @ 25°C

Product Code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LED LYTE IP T NW	Silver	1W	4000K	110°	82	82	46	A t G

Wiring Information

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series

LED Driver

Driver	SELV	Dimming	Bathroom Zone	Min	Max
PLU/PP/350 1-9 (Plug & Play)	Yes	No	1	1	9
PLR/350 1-5	Yes	No	1	1	5
PLD UNI-DRIVE 350mA	Yes	Yes (1-10V)	2	1	10

Accessories

LED LYTE 1M EXT	1m Plug & Play extension lead	Sold Separately
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

C collingwood

Quick and easy installation with plug and play connector

Coastal protected

IP65 ideal for outdoor areas

Guarantee

Features & benefits

- Small & discreet
- Thread and nut for secure fitting

