

## **LED LYTE IP T**

#### **Features** IP65 IP rating **CSP Switchable** Single CCT Tiltable No Dimmable Option Driver dependent L70 70,000h LED Lifetime CRI>80 Colour Rendering Index Colour Consistency SDCM3 **Rotation Angle**

Installation Information			
Input	350mA		
Maximum Ambient Temperature	35°C		
Weight	44g		
Inrush Current	N/A		
Cut Out Size	26		
Construction Material	Anodised aluminium		
UK Bathroom Zone	1		
Electric Class (1, 2, 3)	3		
Suitable for coastal areas	Yes		

#### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LED LYTE IP T NW	Silver	1W	4000K	110°	82	82	46	A f G

### **Wiring Information**

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series

#### **LED Driver**

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A		
PSIP3509W	220-240V	Yes	No	1	1	8

#### **Accessories**

LED LYTE 1M EXT	1m Plug & Play extension lead	Sold Separately
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately

# collingwood



Quick and easy installation with plug and play connector



Coastal protected



IP65 ideal for outdoor areas

#### Guarantee

Warranty	7 yea
----------	-------

#### Features & benefits

- Small & discreet
- Thread and nut for secure fitting





congwoodlighting