LED LYTE IP

IP rated mini LED light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	44g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes
Mounting Options	Wall

PHOTOMETRICS @ 25°C

Product code	W	Colour	Beam	lm	lm/W	Lx @ 1m
LED LYTE IP NW	1W	4000K	110°	82	82	46
LED LYTE IP WW	1W	3000K	110°	63	63	30
LED LYTE IP 27	1W	2700K	110°	58	58	29

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A		
PSIP3509W	220-240V	Yes	No	1	1	8

ACCESSORIES

LED LYTE 1M EXT	1m Plug & Play extension lead	Sold Separately
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately

COLLINGWOOD LIGHTING

LIGHTING INNOVATION

Quick and easy installation with plug and play connector

Coastal protected

IP65 IP65 ideal for outdoor areas

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Small & discreet

Ideal for decorative lighting

BEAM ANGLE: **110°**