# Decorative wall lights + undershelf lighting specification sheet



# **LED LYTE IP**

IP rated mini LED light

Features	
IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Consistency	SDCM3

Installation Information				
Input	350mA			
Maximum Ambient Temperature	35°C			
Weight	44g			
Cut Out Size	Ø 26mm			
Construction Material	Anodised aluminium			
UK Bathroom Zone	1			
Electric Class (1, 2, 3)	3			
Suitable for coastal areas	Yes			

#### Photometrics @ 25°C

Product Code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LED LYTE IP NW	Silver	1W	4000K	110°	82	82	46	A F
LED LYTE IP WW	Silver	1W	3000K	110°	63	63	30	A F
LED LYTE IP 27	Silver	1W	2700K	110°	58	58	29	A C G

# **Wiring Information**

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series

# **LED Driver**

Driver	SELV	Dimming	Bathroom Zone	Min	Max
PLU/PP/350 1-9 (Plug & Play)	Yes	No	1	1	9
PLR/350 1-5	Yes	No	1	1	5
PLD UNI-DRIVE 350mA	Yes	Yes (1-10V)	2	1	10

#### **Accessories**

LED LYTE 1M EXT	1m Plug & Play extension lead	Sold Separately
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



Quick and easy installation with plug and play connector

Coastal protected

IP65 ideal for outdoor areas

#### Guarantee

### Features & benefits

- Small & discreet
- Ideal for decorative lighting

