# Decorative wall lights + undershelf lighting specification sheet



# **LED LYTE SURFACE**

Surface-mount LED mini light

Features	
IP rating	IP65
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	No

Installation Information				
350mA				
35°C				
900g				
N/A				
N/A				
Anodised aluminium				
1				
3				
Yes				

# Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LED LYTE SURFACE NW	Silver	1W	4000K	110°	82	82	46	A F

### **Wiring Information**

<b>J</b>		
Cable / Flying Lead	1m (0.205mm² red & black PTFE)	
Type of Wiring Required	Series	

# **LED Driver**

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/PP/350 1-9 (Plug & Play)	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

## **Accessories**

LED LYTE 1M EXT	1m Plug & Play extension lead	Sold Separately
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

# **C** collingwood



Quick and easy installation with plug and play connector



Coastal protected



IP65 ideal for outdoor areas

## Guarantee

Warranty 7 years

# Features & benefits

- Complete with wall fixings
- Small & discreet, ideal for under cabinet lighting

