



Quick and easy installation with plug and play connector

Coastal protected

IP65 ideal for outdoor areas

LED LYTE SURFACE

Surface-mount LED mini light

Features

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	900g
Cut Out Size	N/A
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

Guarantee

Features & benefits

- Complete with wall fixings
- Small & discreet, ideal for under cabinet lighting

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LED LYTE SURFACE NW	Silver	1W	4000K	110°	82	82	46	

Wiring Information

Cable / Flying Lead	1m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series

LED Driver

Driver	SELV	Dimming	Bathroom Zone	Min	Max
PLU/PP/350 1-9 (Plug & Play)	Yes	No	1	1	9
PLR/350 1-5	Yes	No	1	1	5
PLD UNI-DRIVE 350mA	Yes	Yes (1-10V)	2	1	10

Accessories

LED LYTE 1M EXT	1m Plug & Play extension lead
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
	Sold Separately

