

LED LYTE

Mini LED light

FEATURES

IP rating	IP30
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Consistency	SDCM3
Rotation Angle	No

INSTALLATION INFORMATION

Input	350mA
Maximum Ambient Temperature	35°C
Weight	20g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Plastic
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	3
Suitable for coastal areas	No

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LED LYTE WW	Chrome	1W	3000K	110°	60	60	30	A F
LED LYTE 27		1W	2700K	110°	58	58	29	
LED LYTE RED	Chrome	1W	Red	110°				

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A	1	13
PSIP3509W	220-240V	Yes	No	Outside zones	1	8

ACCESSORIES

LED LYTE 1M EXT	1m Plug & Play extension lead	
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



LIGHTING INNOVATION



Quick and easy installation with plug and play



Coastal protected



IP30 perfect for interior applications

WARRANTY

Warranty

7 yeaı

FEATURES & BENEFITS

Mini LED perfect for small room e.g. closets

Small & discree

