



## LED LYTE

Mini LED light

### Features

IP rating	IP30
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

### Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	20g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Plastic
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	3
Suitable for coastal areas	No

### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LED LYTE NW	Chrome	1W	4000K	110°	82	82	46	
LED LYTE WW	Chrome	1W	3000K	110°	60	60	30	
LED LYTE 27	Chrome	1W	2700K	110°	58	58	29	
LED LYTE RED	Chrome	1W	Red	110°	-	-	-	

### Wiring Information

Cable / Flying Lead	1m (0.205mm <sup>2</sup> red & black PTFE)
Type of Wiring Required	Series

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/PP/350 1-9 (Plug & Play)	220-240V	Yes	No	Outside zones	1	9
PSIP3509W	220-240V	Yes	No	Outside zones	1	8
PSMD35039	220-240V	Yes	Yes (mains)	Outside zones	3	9

### Accessories

LED LYTE 1M EXT	1m Plug & Play extension lead	Sold Separately
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



collingwood



Quick and easy installation with plug and play connector



Coastal protected



IP30 perfect for interior applications

### Guarantee

Warranty 7 years

### Features & benefits

- Mini LED perfect for small room e.g. closets
- Small & discreet

