



LED LYTE

Mini LED light

FEATURES

IP rating	IP30
CSP Switchable	Single CCT
Tilttable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	20g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Plastic
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	III
Suitable for coastal areas	No

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LED LYTE WW	Chrome	1W	3000K	110°	60	60	30	
LED LYTE 27		1W	2700K	110°	58	58	29	
LED LYTE RED	Chrome	1W	Red	110°				

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A	1	13
PSIP3509W	220-240V	Yes	No	Outside zones	1	8

ACCESSORIES

LED LYTE 1M EXT	1m Plug & Play extension lead	Sold Separately
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead	Sold Separately



Quick and easy installation with plug and play connector



Coastal protected



IP30 perfect for interior applications

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Mini LED perfect for small room e.g. closets

Small & discreet

