



collingwood

LEDEP09DA



Self-test device, simple emergency lighting inspections



DALI compatible



Design allows installation through ceiling cut out of 55mm

Features

IP rating	IP20
-----------	------

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	5°C - 35°C
Weight	378g
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	4A 0.55ms
Cut Out Size	55mm
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	2
Install Connector Type	Mains: Push-fit terminals 0.75 - 1.5mm ² DC: Plug & Play connectors

Guarantee

Warranty	5 years
Battery Warranty	3 years

Features & benefits

- Dual colour Green / Red LED status indicator
- Lithium iron phosphate (LiFePO4) battery
- Supplied with a test button, whereby a battery duration test can be carried out at anytime
- Synchronizes an automatic battery duration test every 6 months
- 3-pole isolation of lamp & mains driver power during emergency
- Battery connectors are polarity protected

Photometrics @ 25°C

Product Code	Finish	Type
LEDEP09DA	White	LiFePO4 battery

Wiring Information

Cable / Flying Lead	2x 1mm ² H05VV-F
Type of Wiring Required	Parallel

Accessories

N/A	No accessories are required
-----	-----------------------------

