



## LEDEP10

Emergency converter, Self-test & Manual-test switchable, maintained

### FEATURES

IP rating	IP20
-----------	------

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	5°C - 55°C
Weight	390g
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	II
Case Temperature (tc = °C)	75
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm <sup>2</sup> DC: Plug & Play connectors
Connection Output	DC Plug and Play Connector

### PHOTOMETRICS @ 25°C

Product code	Finish	Type
LEDEP10	Matt white	LiFePO4 battery

### WIRING INFORMATION

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0.5 - 2.5mm <sup>2</sup>
Output Cable Type	DC Plug & Play Connector

### ACCESSORIES

N/A (No Accessories required)
-------------------------------

**Self Test of Manual Test** Self-test and Manual-test switchable

**Battery** LiFePO4, provides long operational life

**EM 3h** A minimum of 3 hours of emergency lighting

### WARRANTY

Warranty	5 years (extended)
Battery Warranty	5 years

### FEATURES & BENEFITS

Built-in protection: - open circuit - over charging - over discharging - over temperature

Dual colour Green / Red LED status indicator

Supplied with a test button, whereby a battery duration test can be carried out at anytime

Synchronizes an automatic battery duration test every 6 months

Compatible with our Solis panels, Thea commercial downlights, H2 Pro, 1901 and H5 downlights, however this does not apply to trimless

