



Self-test and Manual-test switchable



LiFePO₄, provides long operational life



A minimum of 3 hours of emergency lighting

LEDEP10

Emergency converter, Self-test & Manual-test switchable, maintained

FEATURES

IP rating	IP20
------------------	------

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	5°C - 55°C
Weight	390g
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	2
Case Temperature (tc = °C)	75
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm ² DC: Plug & Play connectors
Connection Output	DC Plug and Play Connector

WARRANTY

Warranty	5 years (extended)
Battery Warranty	5 years

FEATURES & BENEFITS

Built-in protection: - open circuit - over charging - over discharging - over temperature

Dual colour Green / Red LED status indicator

Supplied with a test button, whereby a battery duration test can be carried out at anytime

Synchronizes an automatic battery duration test every 6 months

Compatible with our Solis panels, Thea commercial downlights, H2 Pro, 1901 and H5 downlights, however this does not apply to trimless

PHOTOMETRICS @ 25°C

Product code	Finish	Type
LEDEP10	Matt white	LiFePO ₄ battery

WIRING INFORMATION

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0.5 - 2.5mm ²
Output Cable Type	DC Plug & Play Connector

ACCESSORIES

N/A (No Accessories required)

