



## LEDEP10DA

Emergency Converter, DALI, Self-Test, 2.5W

### FEATURES

IP rating	IP20
-----------	------

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	365g
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	II
Case Temperature (tc = °C)	65
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm² DC: Plug & Play connectors
Connection Output	DC Plug and Play Connector

### PHOTOMETRICS @ 25°C

Product code	Finish	Type
LEDEP10DA	Matt white	LiFePO4 battery

### WIRING INFORMATION

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0.5 - 2.5mm²
Output Cable Type	DC Plug & Play Connector

### ACCESSORIES

Compatible with Panel Range	Sold Separately
Compatible with Thea Range	Sold Separately



DALI addressable  
emergency, intelligent  
emergency monitoring



LiFePO4, provides long  
operational life



A minimum of 3 hours of  
emergency lighting

### WARRANTY

Warranty	5 years (extended)
Battery Warranty	5 years

### FEATURES & BENEFITS

Built-in protection: - open circuit - over charging  
- over discharging - over temperature

Dual colour Green / Red LED status indicator

Supplied with a test button, whereby a battery  
duration test can be carried out at anytime

Synchronizes an automatic battery duration  
test every 6 months

