



LEDEP10DA

Emergency Converter, DALI, Self-Test, 2.5W

FEATURES

IP rating	IP20
-----------	------

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	390g
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	2
Case Temperature (tc = °C)	65
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm ² DC: Plug & Play connectors
Connection Output	DC Plug and Play Connector

PHOTOMETRICS @ 25°C

Product code	Finish	Type
LEDEP10DA	Matt white	LiFePO4 battery

WIRING INFORMATION

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0,5 - 2,5mm ²
Output Cable Type	DC Plug & Play Connector

ACCESSORIES

Compatible with Panel Range	Sold Separately
Compatible with Thea Range	Sold Separately



DALI addressible
emergency, intellegent
emergency monitoring



LiFePO4, provides long
operational life



A minimum of 3 hours of
emergency lighting

WARRANTY

Warranty	5 years (extended)
Battery Warranty	5 years

FEATURES & BENEFITS

Built-in protection: - open circuit - over charging
- over discharging - over temperature

Dual colour Green / Red LED status indicator

Supplied with a test button, whereby a battery
duration test can be carried out at anytime

Synchronizes an automatic battery duration
test every 6 months

