



LEDEP10DA

Emergency Converter, DALI, Self-Test, 2.5W

FEATURES

| | |
|-----------|------|
| IP rating | IP20 |
|-----------|------|

INSTALLATION INFORMATION

| | |
|-----------------------------|---|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 0°C - 45°C |
| Weight | 390g |
| Insulation Coverable | No |
| Double Insulation | Yes |
| Inrush Current | 1.5A 0.6ms |
| Cut Out Size | 18 (status LED) 7 (test button) |
| Construction Material | Polycarbonate |
| SELV | Yes |
| Electric Class (1, 2, 3) | II |
| Case Temperature (tc = °C) | 65 |
| Install Connector Type | Mains: Push-fit terminals 0.5 - 2.5mm ² DC: Plug & Play connectors |
| Connection Output | DC Plug and Play Connector |

PHOTOMETRICS @ 25°C

| Product code | Finish | Type |
|--------------|------------|-----------------|
| LEDEP10DA | Matt white | LiFePO4 battery |

WIRING INFORMATION

| | |
|-------------------------|---|
| Cable / Flying Lead | Plug & Play connectors |
| Type of Wiring Required | Parallel |
| Input Cable Type | Push-fit terminals 0.5 - 2.5mm ² |
| Output Cable Type | DC Plug & Play Connector |

ACCESSORIES

| | |
|-----------------------------|-----------------|
| Compatible with Panel Range | Sold Separately |
| Compatible with Thea Range | Sold Separately |



DALI addressable
emergency, intelligent
emergency monitoring



LiFePO4, provides long
operational life



A minimum of 3 hours of
emergency lighting

WARRANTY

| | |
|------------------|--------------------|
| Warranty | 5 years (extended) |
| Battery Warranty | 5 years |

FEATURES & BENEFITS

Built-in protection: - open circuit - over charging
- over discharging - over temperature

Dual colour Green / Red LED status indicator

Supplied with a test button, whereby a battery
duration test can be carried out at anytime

Synchronizes an automatic battery duration
test every 6 months

