



Manual Test device, easy emergency lighting inspections



LiFePO₄, provides long operational life



A minimum of 3 hours of emergency lighting

LEDEP10EM

Emergency converter, Manual-test, 2.5W

Features

IP rating	IP20
-----------	------

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	0°C - 45°C
Weight	360g
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	2
Case Temperature (tc = °C)	75
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm ² DC: Plug & Play connectors
Connection Output	DC Plug and Play Connector

Guarantee

Warranty	5 years (extended)
Battery Warranty	5 years

Features & benefits

- Built-in protection: - open circuit - over charging - over discharging - over temperature
- Dual colour Green / Red LED status indicator
- Supplied with a test button, whereby a battery duration test can be carried out at anytime
- Compatible with our Solis panels, Thea commercial downlights, H2 Pro, 1901 and H5 downlights, however this does not apply to trimless
- IP20

Photometrics @ 25°C

Product Code	Finish	Type
LEDEP10EM	Matt white	LiFePO ₄ battery

Wiring Information

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0,5 - 2,5mm ²
Output Cable Type	DC Plug & Play Connector

Accessories

N/A (No Accessories required)

