



LEDEP11

Emergency converter for H2 and H4 Pro, self-test, maintained.

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	0°C - 50°C
Weight	294g
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	2
Case Temperature (tc = °C)	60
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm ² DC: Plug & Play connectors
Connection Output	Plug & Play

PHOTOMETRICS @ 25°C

Product code	Finish
LEDEP11	Matt white

WIRING INFORMATION

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0.5 - 2.5mm ²
Output Cable Type	DC Plug & Play Connector

Self Test Self-test device, simplifying the inspections

LiFePO4 LiFePO4, provides long operational life

EM 3h A minimum of 3 hours of emergency lighting

WARRANTY

Warranty	3 years (extended)
Battery Warranty	5 years

FEATURES & BENEFITS

Built-in protection: - open circuit - over charging
- over discharging - over temperature

Dual colour Green / Red LED status indicator

Supplied with a test button, whereby a battery duration test can be carried out at anytime

Synchronizes an automatic battery duration test every 6 months

Compatible with our H2 and H4 Pro colour and lumen switchable downlights

IP20

