



Self-test and Manual-test switchable



LiFePO4, provides long operational life



A minimum of 3 hours of emergency lighting

WARRANTY

Warranty	5 years (extended)
Battery Warranty	5 years

FEATURES & BENEFITS

Built-in protection: - open circuit - over charging
- over discharging - over temperature

Dual colour Green / Red LED status indicator

Supplied with a test button, whereby a battery duration test can be carried out at anytime

Synchronizes an automatic battery duration test every 6 months

Compatible with H2 Sense

IP20

LEDEP14

H2 Sense stand alone emergency pack

FEATURES

IP rating	IP20
-----------	------

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	5°C - 35°C
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	2
Case Temperature (tc = °C)	60
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm² DC: Plug & Play connectors
Connection Output	DC Plug and Play Connector

PHOTOMETRICS @ 25°C

Product code	Finish
LEDEP14	Matt white

*Used for Sense lights which are either fitted with plain bezels and controlled by other sensor lights on the circuit, or for standalone lights which have sensor bezels but do not control any other lights.

WIRING INFORMATION

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0.5 - 2.5mm²
Output Cable Type	DC Plug & Play Connector

ACCESSORIES

H2 Sense	H2 Sense CSP, Housing and Driver, IP65 Non-Dim	Sold Separately
----------	--	-----------------

