



collingwood

LEDEP15



Self-test and Manual-test switchable



LiFePO4, provides long operational life



A minimum of 3 hours of emergency lighting

Features

IP rating	IP20
-----------	------

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	5°C - 35°C
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	2
Case Temperature (tc = °C)	60
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm ² DC: Plug & Play connectors
Connection Output	DC Plug and Play Connector

Guarantee

Warranty	5 years (extended)
Battery Warranty	5 years

Features & benefits

- Built-in protection: - open circuit - over charging - over discharging - over temperature
- Dual colour Green / Red LED status indicator
- Supplied with a test button, whereby a battery duration test can be carried out at anytime
- Synchronizes an automatic battery duration test every 6 months
- Compatible with H2 Sense
- IP20

Photometrics @ 25°C

Product Code	Finish
LEDEP15	Matt white

*Used for Sense lights which are fitted with sensor bezels and will be acting as masters to control other lights on the circuit.

Wiring Information

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0.5 - 2.5mm ²
Output Cable Type	DC Plug & Play Connector

Accessories

H2 Sense	H2 Sense CSP, Housing and Driver, IP65 Non-Dim	Sold Separately
----------	--	-----------------

