



Self-test and Manual-test switchable



LiFePO<sub>4</sub>, provides long operational life



A minimum of 3 hours of emergency lighting

## WARRANTY

Warranty	5 years (extended)
Battery Warranty	5 years

## FEATURES & BENEFITS

Built-in protection: - open circuit - over charging  
- over discharging - over temperature

Dual colour Green / Red LED status indicator

Supplied with a test button, whereby a battery duration test can be carried out at anytime

Synchronizes an automatic battery duration test every 6 months

Compatible with H2 Sense

IP20

# LEDEP15

H2 Sense primary switching emergency pack

## FEATURES

IP rating	IP20
-----------	------

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	5°C - 35°C
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	1.5A 0.6ms
Cut Out Size	18 (status LED) 7 (test button)
Construction Material	Polycarbonate
SELV	Yes
Electric Class (1, 2, 3)	2
Case Temperature (tc = °C)	60
Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm <sup>2</sup> DC: Plug & Play connectors
Connection Output	DC Plug and Play Connector

## PHOTOMETRICS @ 25°C

Product code	Finish
LEDEP15	Matt white

\*Used for Sense lights which are fitted with sensor bezels and will be acting as masters to control other lights on the circuit.

## WIRING INFORMATION

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0.5 - 2.5mm <sup>2</sup>
Output Cable Type	DC Plug & Play Connector

## ACCESSORIES

H2 Sense	H2 Sense CSP, Housing and Driver, IP65 Non-Dim	Sold Separately
----------	--	-----------------

