



LEDLINE 400 45

45° wall washing light bar

FEATURES

IP rating	IP65
IK rating	IK02
CSP Switchable	Single CCT
Tiltable	180°
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

INSTALLATION INFORMATION

Input	700mA
Maximum Ambient Temperature	40°C
Weight	0.9kg
Inrush Current	N/A
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LEDLINE 400 NW 45	Black	16W	4000K	45°	1000	63	2629	

WIRING INFORMATION

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700 (all settings)	220-240V	Yes	No	N/A		
PSIP70036W	220-240V	Yes	No	1	1	1
PSDIM700	220-240V	Yes	Yes (1-10V)	1	1	2

ACCESSORIES

JB4 / JB6	Gel filled junction box	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately



16W at 700mA



Coastal protected



IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years (extended)

FEATURES & BENEFITS

45° beam angle ideal for mid-level wall wash

Robust cable for permanent use outdoors

