



RGB



Quick and easy installation with plug and play connector



IP40 suitable for living room and bedrooms

LL030CARGB

Colour change LED unit (4W max.)

Features

IP rating	IP40
CSP Switchable	RGB
LED Lifetime	L50 50,000h

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	50g
Insulation Coverable	No
Cut Out Size	Housing Dependant
Construction Material	Aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	3
Suitable for coastal areas	No
Install Connector Type	Flying lead

Guarantee

Warranty 5 years

Features & benefits

- MR16 for retrofit into existing housings
- Short heatsink for shallow housings
- Compatible with a large range of controllers

Patent Information

GB2487912 GB2512715

RGB Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
LL030CARGB	1W	Red	18°	38	38	319
LL030CARGB	1.2W	Green	18°	75	63	774
LL030CARGB	1.2W	Blue	18°	11	9	9

Wiring Information

Cable / Flying Lead	2x 1m Plug & Play 4-core ribbon cable
Type of Wiring Required	Series
Input Cable Type	Plug & Play 4 Core ribbon cable

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	
CCDRV75DMX	220-240V	Yes	Yes	2	13
CCDRV75RF	220-240V	Yes	Yes	2	13

Accessories

CR575RGBW	5-core PVC cable	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately

