



LSC04

14.4 W/m, IP20, 24V current regulated, high CRI, self-adhesive, flexible strip

Features

| | |
|------------------------|------------------|
| IP rating | IP20 |
| CSP Switchable | Single CCT |
| Dimmable Option | Driver dependent |
| LED Lifetime | L70 60,000h |
| Colour Rendering Index | CRI>90 |
| Colour Consistency | SDCM3 |
| Self-Adhesive Backing | Yes |
| Bespoke Lengths | Yes |
| Strip type | Flexible tape |

Installation Information

| | |
|-----------------------------|---------------|
| Input | 24V DC |
| Maximum Ambient Temperature | -20°C - 40°C |
| Weight | 28g per meter |
| Construction Material | Flexible tape |
| UK Bathroom Zone | N/A |
| Electric Class (1, 2, 3) | 3 |
| Maximum Running Length | 20 m |

Photometrics @ 25°C

| Product Code | Type | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|---------------------------|---------|--------|------|------|------|---------|--------|
| LSC0427100 | 120 LEDs/m Max Run 10m | 14.4W/m | 2700K | 120° | 1200 | 83 | 389 | |
| LSC0430100 | 120 LEDs/m Max Run 10m | 14.4W/m | 3000K | 120° | 1280 | 89 | 414 | |
| LSC0440100 | 120 LEDs/m Max Run 10m | 14.4W/m | 4000K | 120° | 1350 | 94 | 437 | |
| LSC0427600 | 120 LEDs/m Max Run 10m | 14.4W/m | 2700K | 120° | 1200 | 83 | 389 | |
| LSC0430600 | 120 LEDs/m Max Run 10m | 14.4W/m | 3000K | 120° | 1280 | 89 | 414 | |
| LSC0440600 | 120 LEDs/m Max Run 10m | 14.4W/m | 4000K | 120° | 1350 | 94 | 437 | |

Wiring Information

| | |
|-------------------------|--|
| Cable / Flying Lead | Supplied with 500mm, 0.5mm ² flying lead from one end |
| Type of Wiring Required | Parallel |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|-----------|----------|------|-------------------------|---------------|-----|-----|
| LSD6024 | 220-240V | Yes | Yes (with PDCINT 1-10V) | Outside zones | - | 4m |
| LSD12024 | 220-240V | Yes | Yes (with PDCINT 1-10V) | Outside zones | - | - |
| PSIP25024 | 220-240V | Yes | Yes (with PDCINT 1-10V) | Outside zones | - | 17m |

Accessories

| | | |
|-------------------------|--|-----------------|
| LSAFC122 / LSAFCS122 | Range of fast fix connectors for use with LSC04/05/06 | Sold Separately |
| LED STRIP PROFILE RANGE | Profile range to house adhesive strip | Sold Separately |
| LED COVE PACK | Coving to house adhesive strip | Sold Separately |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types | Sold Separately |
| PDCINT1-10V | 1-10V, Push, DALI dimming interface for use with 24V LED drivers | Sold Separately |



collingwood

14.4W

Ideal for primary light with 14.4W/m

IP20

Ideal for living room and hallways with IP20 rating

BESPOKE

Bespoke lengths available


Guarantee

Warranty 5 years

Features & benefits

- Cut points are every 50mm
- 500mm flying leads attached
- Has high quality LED strip using current regulation without experiencing any light drop off
- Long lengths (up to 10m) suffer no light loss
- A foil backed flexible PCB, which dissipates heat (improves LED life and colour stability)
- Quick and easy installation with 3M self-adhesive backing
- High efficacy of 94lm/W
- CRI 90 providing true colour appearance

10m/50mm



12mm