

LSC86

17.0 W/m, IP68, 24V current regulated, high CRI, self-adhesive, waterproof flexible strip

FEATURES

IP rating	IP68
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 60,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Self-Adhesive Backing	Yes
Bespoke Lengths	Yes
Strip type	Flexible tape

INSTALLATION INFORMATION

Input	24V DC		
Maximum Ambient Temperature	-20°C - 40°C		
Weight	126g per meter		
Construction Material	Flexible tape with Silicone		
Construction Material	coating		
UK Bathroom Zone	0		
Electric Class (1, 2, 3)	3		
Maximum Running Length	10 m		

PHOTOMETRICS @ 25°C

Product code	Туре	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LSC8627400	144 LEDs/m Max Run 10m	17W/m	2700K	120°	1250	74	405	A G
LSC8630400	144 LEDs/m Max Run 10m	17W/m	3000K	120°	1350	79	421	A F
LSC8640400	144 LEDs/m Max Run 10m	17W/m	4000K	120°	140	82	453	A F

WIRING INFORMATION

Cable / Flying Lead	Supplied with 500mm, 0.5mm² flying lead from one end			
Type of Wiring Required	Parallel			

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PS7524	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	-	3m
PSIP15024	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	-	8m
PSIP25024	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	-	14m

ACCESSORIES

LED STRIP PROFILE RANGE	Profile range to house adhesive strip	Sold Separately
PDCINT1-10V	1-10V, Push, DALI dimming interface for use with 24V LED drivers	Sold Separately



LIGHTING INNOVATION



Ideal for primary light with 17W/m



Ideal for wet environments with IP68



Bespoke lengths available

WARRANTY

FEATURES & BENEFITS

Has high quality LED strip using current regulation without experiencing any light drop

High-grade silicone extruded coating, UV

10m/41.6mm

14x5mm