

LSR05

Colour change, self-adhesive flexible strip (15W max.)

FEATURES

IP rating	IP20
CSP Switchable	RGBW
Tiltable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Self-Adhesive Backing	True
Bespoke Lengths	Yes
Strip type	Flexible tape

INSTALLATION INFORMATION

Input	24V DC
Weight	20g per meter
Construction Material	Flexible tape
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	III
Suitable for coastal areas	No
Maximum Running Length	5 m

WIRING INFORMATION

Cable / Flying Lead	0.2m 5-core ribbon cable
Type of Wiring Required	Parallel
Input Cable Type	5 core ribbon cable

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PR3002	220-240V	Yes	Yes	N/A	0.1m	2x 5m
ACCESSORIES						

CR575RGBW	5-core PVC cable	Sold Separately
CF505RGBW	5-core RGBW ribbon cable	Sold Separately
LED STRIP PROFILE RANGE	Profile range to house adhesive strip	Sold Separately



LIGHTING INNOVATION



Ideal for accent lighting with low wattage

RGBW

IP**20**

IP20 ideal for living room and hallways

WARRANTY

FEATURES & BENEFITS

IP20 ideal for living room and hallways
Hard-wearing clear covering
Foil backed flexible PCB dissipates heat
(improves LED life and colour stability)
50 LEDs per mete in White and RGBW for an
even spread of light
3M self-adhesive backing
Supplied in customised lengths (0.1m up to 4.9m
in 100mm increments) 5m reel also available
Compatible with a large range of controllers

<u>5m/100mm</u>

<u>12m</u>n