

**14.4W/m** Ideal for primary light with 14.4W/m

**IP44** Ideal for kitchen and bathroom with IP44 rating

**...** Bespoke lengths available

## WARRANTY

Warranty 1 year

## FEATURES & BENEFITS

Excellent for primary lighting and within coving

Cut points every 100mm

3M self-adhesive backing for secure and easy installation

Supplied in a resealable, antistatic bag to protect during transit

# LSV44

Constant voltage, IP44, self-adhesive 5m LED strip

## FEATURES

IP rating	IP44
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Self-Adhesive Backing	True
Bespoke Lengths	Yes
Strip type	Flexible tape

## INSTALLATION INFORMATION

Input	24V DC
Maximum Ambient Temperature	40°C
Weight	196g per meter
Construction Material	Flexible tape with PU coating
UK Bathroom Zone	2
Electric Class (1, 2, 3)	III
Maximum Running Length	5 m

## PHOTOMETRICS @ 25°C

Product code	W	Colour	Beam	lm	lm/W	Lx @ 1m
LSV4435050	14.4W/m	3500K	100°	1200	80	225

Energy rating is a reflection of the LED light source.

## WIRING INFORMATION

Cable / Flying Lead	Supplied with a minimum of 200mm flying lead from one end
Type of Wiring Required	Parallel


## LED DRIVER

Driver	Input	SELV	Dimming	Max
PS5024	220-240V	Yes	Yes (with PDCINT 1-10V)	3m
PS7524	220-240V	Yes	Yes	5m
PSIP24024	220-240V	Yes	Yes	3 x 5m

## ACCESSORIES

LED STRIP PROFILE RANGE	Profile range to house adhesive strip	Sold Separately
LED COVE PACK	Coving to house adhesive strip	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers	Sold Separately

BEAM ANGLE: **100°**



5m/100mm



10mm