



LSV45

Constant voltage, self-adhesive, flexible IP44 strip

Features

IP rating	IP44
CSP Switchable	Single CCT
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Self-Adhesive Backing	Yes

Installation Information

Input	24V DC
Maximum Ambient Temperature	40°C
Weight	150g per meter
Construction Material	Flexible tape
UK Bathroom Zone	2
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product Code	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
LSV4540050	5m reel 120 LED's/m	9.6W/m	4000K	120°	950	99	299	
LSV4530050	5m reel 120 LED's/m	9.6W/m	3000K	120°	860	90	271	
LSV4527050	5m reel 120 LED's/m	9.6W/m	2700K	120°	830	87	262	

Wiring Information

Cable / Flying Lead	Supplied with a minimum of 200mm flying lead from one end
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PS5024	220-240V	Yes	Yes (with PDCINT 1-10V)	-	-	5m
PSIP24024		Yes	Yes	-		4 x 5m
PSDIP10024		Yes	Yes	-		2 x 5m

Accessories

LED STRIP PROFILE RANGE	Profile range to house adhesive strip
LED COVE PACK	Coving to house adhesive strip
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
PDCINTI-10V	1-10V dimming interface for use with 24V LED drivers



collingwood

Ideal for atmospheric light with 9.6W/m

Ideal for kitchen and bathroom with IP44 rating

Bespoke lengths available

Guarantee

Features & benefits

- Excellent for accent lighting
- Cut points every 50mm
- Quick and easy installation with 3M self-adhesive backing
- High efficacy of 99lm/W
- Enlarged connection points for ease of installation
- Has a UV resistant, silicone coating to enable cleaning

5m/50mm

