

**9.6W/m** Ideal for atmospheric light with 9.6W/m

**IP44** Ideal for kitchen and bathroom with IP44 rating

**...** Bespoke lengths available

## WARRANTY

Warranty 3 years

## FEATURES & BENEFITS

Excellent for accent lighting

Cut points every 50mm

Quick and easy installation with 3M self-adhesive backing

High efficacy of 99lm/W

Enlarged connection points for ease of installation

Has a UV resistant, silicone coating to enable cleaning

# LSV45

Constant voltage, self-adhesive, flexible IP44 strip

## FEATURES

<b>IP rating</b>	IP44
<b>CSP Switchable</b>	Single CCT
<b>Dimmable Option</b>	Driver dependent
<b>LED Lifetime</b>	L70 30,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM5
<b>Self-Adhesive Backing</b>	Yes
<b>Bespoke Lengths</b>	Yes
<b>Strip type</b>	Flexible tape

## INSTALLATION INFORMATION

<b>Input</b>	24V DC
<b>Maximum Ambient Temperature</b>	-20°C - 45°C
<b>Weight</b>	32g per meter
<b>Construction Material</b>	Flexible tape with Silicone coating
<b>UK Bathroom Zone</b>	1
<b>Electric Class (1, 2, 3)</b>	3
<b>Maximum Running Length</b>	5 m

## PHOTOMETRICS @ 25°C

Product code	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
<b>LSV4540050</b>	5m reel 120 LED's/m	9.6W/m	4000K	120°	950	99	299	
<b>LSV4530050</b>	5m reel 120 LED's/m	9.6W/m	3000K	120°	860	90	271	
<b>LSV4527050</b>	5m reel 120 LED's/m	9.6W/m	2700K	120°	830	87	262	

## WIRING INFORMATION

<b>Cable / Flying Lead</b>	Supplied with 500mm, 0.5mm <sup>2</sup> flying lead from one end
<b>Type of Wiring Required</b>	Parallel

## LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
LSD6024	220-240V	Yes	Yes (with PDCINT 1-10V)	1 (If no water jets)	-	6m
LSD12024	220-240V	Yes	Yes (with PDCINT 1-10V)	1 (If no water jets)	-	-
PSIP25024	220-240V	Yes	Yes (with PDCINT 1-10V)	1 (if no water jets)	-	26m

## ACCESSORIES

<b>LED STRIP PROFILE RANGE</b>	Profile range to house adhesive strip	Sold Separately
<b>PDCINT1-10V</b>	1-10V dimming interface for use with 24V LED drivers	Sold Separately

5m/50mm



8mm