Low bay specification sheet







Linear Low Bay lighting, dimmable as standard 3-in-1

Features	
IP rating	IP40
IK rating	IK08
CSP Switchable	Single CCT
Sensor Option	PIR with accessory
Dimmable Option	Yes
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	Yes

Installation Information			
Input	220-240V AC		
Maximum Ambient Temperature	0°C - 40°C		
Weight	100W - 2.57Kg 150W - 2.70Kg		
Inrush Current	100W - 70A 0.2ms 150W -		
	110A 0.2ms		
Construction Material	Aluminium / PC		
SELV	Yes		
Electric Class (1, 2, 3)	1		
Install Connector Type	Std - Flying Lead EM - Push-		
mstan Connector Type	fit Term		
UK Building Regulations	Part P		
	Standard - Flying Lead,		
Connection Output	Emergency - Push-fit		
	connector		
Mounting Options	Ceiling & suspended		

Photometrics @ 25°C

Product Code	Finish	Туре	w	Colour	Beam	lm	lm/W	EM lm	Energy
LB10040	White	Standard	100W	4000K	120°	15000	150	-	A E
LB10040E	White	Emergency	100W	4000K	120°	15000	150	340	Å E

Wiring Information

Cable / Flying Lead	Standard: 400mm H05RN-F 3x1.0mm² Ø7mm br/>Emergency: Push-fit terminals 4x 0.75-2.5mm²
Type of Wiring Required	Parallel
Series / Parallel	Parallel

LED Driver

SELV			
Yes			

Accessories

LBAL90	Replacement Lens 90° beam angle	Sold Separately
LBAL5090	Replacement Lens 50°x90° beam angle	Sold Separately
LBAS	Surface mount kit	Sold Separately
PIRBOLTDIM	Dimming PIR Sensor with Lux Level switch 0-2000lx	Sold Separately
PIRBOLTDIMR	Remote control for use with PIRBOLTDIM	Sold Separately

C collingwood



High efficacy of 150lm/W



Very light weight 2.5kg for easy installation



Emergency option available

Guarantee

Warranty	5 year
Battery Warranty	2 year

Features & benefits

- A range of mounting options available allowing excellent flexibility on installation
- Specifically designed for use in aisle spaces
- 1-10V, PWM and resistor dimmable as standard, 3-in-1
- Surge Protection L/N-PE = 10KV L-N = 6KV
- A range of accessories available
- 2m suspension hanging kit inculded
- Emergency Options Self-test as standard, with Manual tests available



