

IP54 IP54 perfect for internal applications

CRI>80 CRI 80 providing true colour appearance

DIM TRIAC Dimmable

WARRANTY

Warranty 5 years

FEATURES & BENEFITS

- Ceiling or suspended mounting option's
- 120° beam angle for wide illumination
- IK06 for impact protection
- Concentric circles create a striking decorative light effect
- Available in both white and black



LUSTRE CEILING LIGHT

A circular decorative ceiling pendant light

FEATURES

| | |
|-------------------------------|-------------|
| IP rating | IP54 |
| IK rating | IK06 |
| CSP Switchable | Single CCT |
| Tiltable (°) | Fixed |
| Dimmable Option | Yes (TRIAC) |
| LED Lifetime | L70 54,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM6 |
| Emergency Option | No |
| Rotation angle (°) | Fixed |

INSTALLATION INFORMATION

| | |
|------------------------------------|--------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | -20°C - 45°C |
| Weight | 1.1kg |
| Inrush Current | 4.52A |
| Construction Material | Polycarbonate |
| UK Bathroom Zone | N/A |
| SELV | No |
| Electric Class (1, 2, 3) | II |
| Install Connector Type | Loop in / Loop out |
| UK Building Regulations | Part P, L |
| Mounting Options | Ceiling |
| Part B Fire Rating | N/A |

PHOTOMETRICS @ 25°C

| Product code | Finish | Type | W | Colour | Beam | lm | lm/W | Energy |
|--------------|--------|-----------------|-----|--------|------|------|------|--------|
| AIN3KCLWHWH | White | White Reflector | 18W | 3000K | 120° | 1000 | 56 | |
| AIN3KCLWHGD | White | Gold Reflector | 18W | 3000K | 120° | 1000 | 56 | |
| AIN3KCLBKWH | Black | White Reflector | 18W | 3000K | 120° | 1000 | 56 | |
| AIN3KCLBKGD | Black | Gold Reflector | 18W | 3000K | 120° | 1000 | 56 | |

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

| | |
|-------------------------------------|--|
| Cable / Flying Lead | N/A |
| Cable Required for Connector | Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm?) or 3-core cable (R02V 3x1.5mm?) |
| Type of Wiring Required | Parallel |

ACCESSORIES

N/A (No Accessories required)

