



C
collingwood

- IP20** IP20 perfect for internal applications
- >80Ra** CRI 80 providing true colour appearance
- Dim** TRIAC Dimmable

Lustre Pendant

A circular decorative pendant light

Features

IP rating	IP20
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	Yes (TRIAC)
LED Lifetime	L70 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	No
Rotation Angle	No
Pendant Cable Length	1,500 mm

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	1.12Kg
Inrush Current	2.32A
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P, L
Mounting Options	Suspended

Guarantee

Warranty 5 years

Features & benefits

- Suspended mounting only
- 120° beam angle for wide illumination
- Concentric circles create a striking decorative light effect
- Available in both white and black

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
AIN3KPLWHWH	White	White Reflector	15W	3000K	120°	1120	76	
AIN3KPLWHGD	White	Gold Reflector	15W	3000K	120°	700	46	
AIN3KPLBKWH	Black	White Reflector	15W	3000K	120°	1120	76	
AIN3KPLBKGD	Black	Gold Reflector	15W	3000K	120°	700	46	

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	N/A
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm?) or 3-core cable (R02V 3x1.5mm?)
Type of Wiring Required	Parallel

Accessories

N/A (No Accessories required)

