





LUSTRE PENDANT

A circular decorative pendant light

FEATURES

IP rating	IP20
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	Yes (TRIAC)
LED Lifetime	L70 54,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	No
Rotation angle (°)	Fixed
Pendant Cable Length	1,500 mm

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	1.32kg
Inrush Current	2.32A
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	No
Electric Class (1, 2, 3)	I
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P, L
Mounting Options	Suspended
Part B Fire Rating	N/A

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
AIN3KPLWHWH	White	White Reflector	15W	3000K	120°	1120	76	D
AIN3KPLWHGD	White	Gold Reflector	15W	3000K	120°	700	46	C
AIN3KPLBKWH	Black	White Reflector	15W	3000K	120°	1120	76	D
AIN3KPLBKGD	Black	Gold Reflector	15W	3000K	120°	700	46	C

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	N/A
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm?) or 3-core cable (R02V 3x1.5mm?)
Type of Wiring Required	Parallel

ACCESSORIES

N/A (No Accessories required)

COLLINGWOOD LIGHTING

LIGHTING INNOVATION

IP20 perfect for internal applications

CRI 80 providing true colour appearance

TRIAC Dimmable

WARRANTY

Warranty 5 years

FEATURES & BENEFITS

- Suspended mounting only
- 120° beam angle for wide illumination
- Concentric circles create a striking decorative light effect
- Available in both white and black



