

-  IP20 perfect for internal applications
-  >80Ra CRI 80 providing true colour appearance
-  TRIAC Dimmable

Lustre Wall Light

A triangular decorative wall light

Features

IP rating	IP20
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	Yes (TRIAC)
LED Lifetime	L70 60,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	No
Rotation Angle	No

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 45°C
Weight	0.48Kg
Inrush Current	3.44A
Construction Material	Aluminium Die-casting
UK Bathroom Zone	N/A
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Loop in / Loop out
UK Building Regulations	Part P, L
Mounting Options	Wall



Guarantee

Warranty 5 years

Features & benefits

- Wall mounting only
- 120° beam angle for wide illumination
- Able to through wire to create your own decorative wall installations. Combine 5 luminaires for a full circle or alternate orientation for a striking luminaire design
- Available in both white and black

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Energy
AIN3KWLWH	White	8W	3000K	120°	480	63	
AIN3KWLBK	Black	8W	3000K	120°	355	49	

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	N/A
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm?) or 3-core cable (R02V 3x1.5mm?)
Type of Wiring Required	Parallel

Accessories

N/A (No Accessories required)

