

IP20

IP20 perfect for internal applications

CRI>80

CRI 80 providing true colour appearance

DIM

TRIAC Dimmable

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Wall mounting only

120° beam angle for wide illumination

Able to through wire to create your own decorative wall installations. Combine 5 luminaires for a full circle or alternate orientation for a striking luminaire design

Available in both white and black

LUSTRE WALL LIGHT

A triangular decorative wall light

FEATURES

| | |
|------------------------|-------------|
| IP rating | IP20 |
| CSP Switchable | Single CCT |
| Tilttable (°) | Fixed |
| Dimmable Option | Yes (TRIAC) |
| LED Lifetime | L70 60,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM6 |
| Emergency Option | No |
| Rotation angle (°) | Fixed |

INSTALLATION INFORMATION

| | |
|-----------------------------|-----------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | -20°C - 45°C |
| Weight | 0.48Kg |
| Inrush Current | 3.44A |
| Construction Material | Aluminium Die-casting |
| UK Bathroom Zone | N/A |
| SELV | No |
| Electric Class (1, 2, 3) | I |
| Install Connector Type | Loop in / Loop out |
| UK Building Regulations | Part P, L |
| Mounting Options | Wall |
| Part B Fire Rating | N/A |

PHOTOMETRICS @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | Energy |
|--------------|--------|----|--------|------|-----|------|---------|
| AIN3KWLWH | White | 8W | 3000K | 120° | 480 | 63 | A t g E |
| AIN3KWLBK | Black | 8W | 3000K | 120° | 355 | 49 | A t g D |

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

| | |
|------------------------------|--|
| Cable / Flying Lead | N/A |
| Cable Required for Connector | Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm?) or 3-core cable (R02V 3x1.5mm?) |
| Type of Wiring Required | Parallel |

ACCESSORIES

| |
|-------------------------------|
| N/A (No Accessories required) |
|-------------------------------|

