

MC010 S

Mini cube LED wall light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	360

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	100g
Cut Out Size	Ø 20mm
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III

PHOTOMETRICS @ 25°C

Product code	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MC010 S 27	1W	2700K	12°	53	53	1425	A G

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	0.15m(0.205 mm² red&blackPTFE)

LED DRIVER

Driver	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	Yes	No	1	1	9
PLR/350 1-5	Yes	No	1	1	5
PLD UNI-DRIVE 350MA	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



LIGHTING INNOVATION

Quick and easy installation with bespoke wall plug

1\٨

IP65 ideal for outdoor areas

FEATURES & BENEFITS

Mini cube spot light for discreet accent lighting of interior and exterior spaces

Quality brushed aluminium finish

Requires 20mm drill b