Decorative wall lights + undershelf lighting specification sheet



MC010 S

Mini cube LED wall light

IP65
Single CCT
No
L70 70,000h
CRI>80
SDCM3
360°

Installation Information			
Maximum Ambient Temperature	35°C		
Weight	100g		
Inrush Current	N/A		
Cut Out Size	20		
Construction Material	Anodised aluminium		
UK Bathroom Zone	1		
Electric Class (1, 2, 3)	3		

Photometrics @ 25°C

Product Code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MC010 S WW	Silver	1W	3000K	12°	55	55	1466	A f G
MC010 S 27	Silver	1W	2700K	12°	53	53	1425	A F
MC010 S RED	Silver	1W	Red	12°				

Wiring Information

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

Accessories

CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately

C collingwood



Quick and easy installation with bespoke wall plug



1W



IP65 ideal for outdoor areas

Guarantee

Warranty 7 years

Features & benefits

- Mini cube spot light for discreet accent lighting of interior and exterior spaces
- Quality brushed aluminium finish
- Requires 20mm drill bit

