Decorative wall lights + undershelf lighting specification sheet



MC010 S

Mini cube LED wall light

Features				
IP rating	IP65			
CSP Switchable	Single CCT			
Dimmable Option	Driver dependent			
LED Lifetime	L70 70,000h			
Colour Rendering Index	CRI>80			
Colour Consistency	SDCM3			
Rotation Angle	360°			
CSP Switchable Dimmable Option LED Lifetime Colour Rendering Index Colour Consistency	Single CCT Driver dependent L70 70,000h CRI>80 SDCM3			

Installation Information			
Input	350mA		
Maximum Ambient Temperature	35°C		
Weight	100g		
Cut Out Size	Ø 20mm		
Construction Material	Anodised aluminium		
UK Bathroom Zone	1		
Electric Class (1, 2, 3)	3		

Photometrics @ 25°C

Product Code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MC010 S WW	Silver	1W	3000K	12°	55	55	1466	A f G
MC010 S 27	Silver	1W	2700K	12°	53	53	1425	A F
MC010 S RED	Silver	1W	Red	12°	-	-	-	

Wiring Information

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	0.15m(0.205 mm² red&blackPTFE)

LED Driver

Driver	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	Yes	No	1	1	9
PLR/350 1-5	Yes	No	1	1	5
PLD UNI-DRIVE 350MA	Yes	Yes (1-10V)	2	1	10

Accessories

CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



Quick and easy installation with bespoke wall plug

1W

IP65 ideal for outdoor areas

Guarantee

Features & benefits

- Mini cube spot light for discreet accent lighting of interior and exterior spaces
- Quality brushed aluminium finish
- Requires 20mm drill bit

