

MC020 S

Up / down mini cuboid LED wall light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	360

INSTALLATION INFORMATION

350mA DC
35°C
200g
N/A
20
Anodised aluminium
1
III
Wall

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MC020 S NW	Silver	2W	4000K	12°	140	70	1485	A C
MC020 S WW	Silver	2W	3000K	12°	110	55	1466	A F
MC020 S RED	Silver	2W	Red	12°				

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	0.15m(0.205 mm² red&blackPTFE)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP3509W	220-240V	Yes	No	1	1	8

ACCESSORIES

CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



LIGHTING INNOVATION



Quick and easy installation with bespoke wall plug



2W at 350mA



IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Bi-directional mini cube for discreet accent lighting of interior and exterior spaces

Quality brushed aluminium finish

Requires 20mm drill bi

